

Lone Star ALS

Crank Description: Lone Star RM Cranks			Max location	Min location	Max cwt travel		
Crank ID No	Wt./ea (lbs)	Moment due to cranks, in-lbs	Counterweight No.	Wt./ea (lbs)	of position arrow	of position arrow	Distance, inch
R4090	4090	350,104	No.4	3247	67	9	58
			No.5	2756	66.7	8.6	58.1
			No.6	2205	69	7	62
			No.7	1653	72	6	66
			No.8	1212	75	3.5	71.5
			No.9	850	77.8	2	75.8
R4619	4619	392,615	No.4	3247	66.7	9	57.7
			No.5	2756	66.4	8.6	57.8
			No.6	2205	68.7	7	61.7
			No.7	1653	71.7	6	65.7
			No.8	1212	74.7	3.5	71.2
			No.9	850	77.5	2	75.5
R5192	5192	441,320	No.4	3247	66.6	9	57.6
			No.5	2756	66.3	8.6	57.7
			No.6	2205	68.6	7	61.6
			No.7	1653	71.6	6	65.6
			No.8	1212	74.6	3.5	71.1
			No.9	850	77.4	2	75.4
R5976	5976	603,935	No.0	6400	75	15.2	59.8
			No.1	5280	79.3	11	68.3
			No.2	4211	80.5	10	70.5
			No.3	3582	83.5	9	74.5
			No.4	3247	83.5	9	74.5
			No.5	2756	83.5	8.6	74.9
			No.6	2205	85.6	7	78.6
			No.7	1653	88.5	6	82.5
			No.8	1212	92	3.5	88.5
R6168	6168	621,734	No.0	6400	74.6	15.2	59.4
			No.1	5280	78	11	67
			No.2	4211	79	10	69
			No.3	3582	82.1	9	73.1
			No.4	3247	82.1	9	73.1
			No.5	2756	82	8.6	73.4
			No.6	2205	84.3	7	77.3
			No.7	1653	87.2	6	81.2
			No.8	1212	90.6	3.5	87.1
			No.9	850	93	2	91