

Since 1919



JENSEN

A DIVISION OF
JENSEN INTERNATIONAL, INC.

JUNE 1997

JENSEN LOW PROFILE PUMPING UNIT

STROKE ADJUSTMENTS: Model 25 or 40A67L24

Crank in bottom hole; Beam in forward hole	24"
Crank in bottom hole; Beam in back hole	20.31"
Crank in top hole; Beam in forward hole	15.70"
Crank in top hole; Beam in back hole	13.49"

STROKE ADJUSTMENTS: Model 25 or 40A67L30

Crank in bottom hole; Beam in forward hole	30"
Crank in bottom hole; Beam in back hole	23.90"
Crank in top hole; Beam in forward hole	19.47"
Crank in top hole; Beam in back hole	15.82"

Model 25/40A67L24 EFFECTIVE COUNTERBALANCE

Structural Unbalance 200 lbs.

**No. Beam Weights Effective Counterbalance
 at Polished rod Pounds**

0-----	250
1-----	550
2-----	870
3-----	1190
4-----	1500
5-----	1790
6-----	2080
7-----	2390
8-----	2690
9-----	2990
10-----	3300
11-----	3610
12-----	3910
13-----	4210
14-----	4520
15-----	4820
16-----	5130

P.O. BOX 1509 ■ COFFEYVILLE, KANSAS 67337 ■ PHONE (316) 251-5700 ■ FAX 316-251-3622
E-MAIL general@jensen-products.com ■ WEB SITE www.jensen-products.com

"Products Serving the World Into the 21st Century"

Since 1919



JENSEN

A DIVISION OF
JENSEN INTERNATIONAL, INC.

***** FACSIMILE TRANSMISSION *****

DATE : 12-15-09

COMPANY : Ram Head

FAX 361-664-8738

CITY : Alice, La

No. of Pages 3

ATTEN: : Mr. Romario Lyle

SUBJECT: #40 A67L24 Low Profile Unit
Counter Balance Sheet

If you have any Questions Please
Call.

Jensen 40A67L24

Model 259000

Serial Number 9710012

FROM: Charles H. Marler
JENSEN INTERNATIONAL
PUMP JACK SALES
1-800-331-2662 Ext. 138
FAX 620-251-6158
"E" Mail charlesm@jensen-products.com

P.O. BOX 1509 ■ COFFEYVILLE, KANSAS 67337 ■ PHONE (620) 251-5700 ■ FAX (620) 251-3622
E-MAIL general@jensen-products.com ■ WEB SITE www.jensen-products.com

"Products Serving the World Into the 21st Century"